

COMPATIBLE WITH UP TO 2 001 DIFFERENT MID WALL A/C MODELS

- Replaces damaged or obsolete remotes*
- Simple set up*
- LCD Display*
- Multi Function*
- Dehumidification*
- Accurate temperature control*
- Fan swing select*
- Fan speed select*
- Heating and Cooling*
- Auto self diagnostics*
- Anti short cycle timer*


KT - 508
508 in 1

KT - 518
518 in 1

KT - 828
2 001 in 1
Instructions:
Programming: Option 1: [Manual setup]

Insert 2 x NEW AAA batteries

Identify the model of the A/C unit and find corresponding code on back of the controller packaging. Point the Remote at the A/C unit. Press the [SEL select] button, Model number at the bottom of the display will flash, use the + or - button to scroll to the first corresponding code an audible beep should sound indicating that the controller and A/C unit are communicating, press enter. Test all functions, in the event of more than 1 code for a manufacturer and all functions do not respond try the next code keep trying until functions respond.

Option 2: [auto search]

Insert 2 x NEW AAA batteries

In the event that the code is not listed or you are unable to establish the exact model. Point the remote at the A/C unit. Press the [SEL select] button, Model number at the bottom of the display will flash, use the [SEL select] button repeatedly to scroll through the code numbers until an audible beep sounds indicating that the controller and A/C unit are communicating, press enter. Test all functions, in the event of more than 1 code for a manufacturer and all functions do not respond try the next code keep trying until functions respond.

Mode Selection button: Auto mode/ unit will heat when room temperature is below 21°C and cool when room temperature is above 27 C.°

Fan Selection button: LOW fan speed when: Unit is in DE-HUMIDIFY or HEAT mode when compressor is either off or in 3 minute delay on start up.

AUTO fan speed. HIGH when temperature differential between set point and room temperature is greater than 4 C.
 LOW when this differential is less than 2 C°

Temperature set button: Adjustable between 15°C - 30°C
 Not adjustable in AUTO or DE HUMIDIFY modes.

Timer button: Set 1 - 16 hours

Swing button: Select swing on / off

Sleep button: Shut down after set time

Too Warm / Cool button: Only available in AUTO mode. Temperature adjustment in increments of 1°C when button depressed

On /Off button: On / Off control



consultaire marketing

Tel: +27 11 674 4011/2/3/ - Fax: +27 11 674 4016

e-mail: info@consultaire.co.za - www.consultaire.co.za