



SW Series

Submersible Water Pumps



Robust Construction

With the choice of stainless steel or plastic casing the SW range is strike resistant and anti corrosion even when used in salt water. High quality resin on the windings ensures long life and that the unit is safe from electricity leakage.

Optional Float Switch

For applications that require the pump to start and stop automatically the SW4500F and SW7000F are supplied complete with float switch.

Application ideas

Application ideas include sewage aeration, water drainage, rain water harvesting and flood prevention.

performance

model no	max flow (l/hr)	max jet (m)
SW2500	2500	3.2
SW4500	4500	4.2
SW4500F	4500	4.2
SW7000F	7000	6.1

voltage

230V 50Hz

specification

model no	Power (w)	Weight (Kg)
SW2500	100	3.3
SW4500	150	4.8
SW4500F	150	5.0
SW7000F	240	5.0

outlet connectors

All pumps are supplied with a choice of two outlet connectors

SW2500	20 / 24.5 mm
SW4500	21.5 / 27.0 mm
SW4500F	21.7 / 27.0 mm
SW7000F	16.0 / 20.0 mm

Dimensions

SW2500	145 x 145 x 230 mm
SW4500	165 x 165 x 255 mm
SW4500F	178 x 178 x 245 mm
SW7000F	178 x 178 x 245 mm

SW Series Applications

